

ESCO

WORLD CLASS. WORLDWIDE.



CelCulture® CO₂ Incubator with Suppressed O₂

CRADLE for BEAUTIFUL CELLS

VivoCell™ Precise Temp, CO₂ Control, O₂ Control and High Humidity: Stable, uniform distribution; fast recovery after door opening without overshoot.

CelSafe™ Robust Contamination Control: ULPA filter enables rapid recovery to ISO Class 5 conditions; 90°C moist heat overnight decon. cycle (HPA validated!); full stainless steel interior, ISOCIDE antimicrobial coating on exterior surfaces; all gas inputs are filtered via 0.2 micron in-line filter.

Intelligent Data & Event Logger: Records all incubator parameters for on screen recall.

CelAlert™ Alarm System: Reminds user to replace expired / depleted parts; ULPA filter replacement reminder alarm; CO₂ tank low alarm; low CO₂ alarm.

Celculture CO₂ Incubator Model CCL-170T_

Temperature	
Temp. Control Method	Direct heat & air jacket
Temp. Range, °C	Amb. +3 to 60
Temp. Uniformity, °C	<± 0.2
Temp. Accuracy, °C	<± 0.1
Recovery Time Without Overshoot* (after 1 min. door opening)	6 mins
Ambient Temp. Range	18 to 34°C (64 to 93 °F)
CO ₂	
CO ₂ Control System	Microprocessor PID
CO ₂ Range, % CO ₂	0-20.7
CO ₂ Accuracy, % CO ₂	± 0.1
CO ₂ Sensor	IR sensor
CO ₂ Recovery Time Without Overshoot** (after 1 min. door opening)	Standard Unit: 4 minutes
CO ₂ Recovery Time Without Overshoot (after 30 seconds door opening)	with Suppressed O ₂ : 5 minutes
O ₂	
O ₂ Control System	Microprocessor PID
O ₂ Range, % O ₂	1-20.7
O ₂ Accuracy, % O ₂	± 0.1
O ₂ Sensor	Galvanic Cell Type
O ₂ Recovery Time (after 30 sec. door opening)	at 1.0 % O ₂ by vol: 20 mins at 5.0 % O ₂ by vol: 10 mins
Humidity	
Humidification Method	Humidity pan
Humidity Range, % RH	Up to 97%
Humidity Recovery Standard Model (- 5% from initial)	20 mins
Humidity Recovery with Suppressed O ₂ Model (- 5% from initial)	45 mins
Physical Construction	
Interior Volume	170 l (5.7 cu.ft.)
External Dimensions (W x D x H)	660 x 660 x 900 mm 26.0" x 26.0" x 35.4"
Internal Dimensions (W x D x H)	505 x 530 x 635 mm 19.9" x 20.9" x 25.0"
Shipping Weight	120 kg (264.6 lbs)
Shipping Dimensions (W x D x H)	850 x 720 x 1150 mm 33.5" x 28.3" x 45.3"
Number of Shelves	4
Maximum No. of Shelves	7
Shelves Area (W x D)	470 x 470 mm (18.5" x 18.5")
Max. Load per Shelf	11 kg/shelf (24.3 lbs/shelf)
Available Electrical Configuration	230 VAC, 50/60 Hz, 1ϕ, 3.4 A 115 VAC, 50/60 Hz, 1ϕ, 7.0 A
Power Consumption	800 watts
Effective Watt at 37°C	80 watts
Contamination Control	
Interior Material	Stainless steel, type 304
Contamination Control Methods	1) Main body is electrogalvanized steel with ISOCIDE antimicrobial coating; 2) ULPA filter; 3) Moist 90°C OVERNIGHT decon. cycle (HPA validated)

Units were factory tested under controlled environmental conditions per Esco method. Esco does not guarantee identical results in the field under differing conditions. Original report available upon request. Model used in the test is CCL-170B-8.

* For temperature not exceeding 37.3°C

** For CO₂ not exceeding 5.2%

Recovery time with TC Sensor is longer



Core Applications:

- Stem Cells
- In-Vitro Fertilization
- Primary Cell Lines
- Cancer Research

Other Features

- Interactive LCD screen
- Continuous data logging controller; quick change of alarm settings; diagnostic interface; password protection; error logging; on-screen quick help
- Air-tight seal door system
- Chamber with rounded corners for easy cleaning
- Pilaster shelving system
- 2 years warranty

Accessories and Options

- Humidity display
- CO₂ analyzer
- CO₂ gas backup
- N₂ gas backup
- Extra shelf
- Analog output
- Reverse door swing
- Roller base
- Stacking kit
- 2-stage gas regulator
- IQ/OQ documentation
- Sealed inner door kit (multi-glass door)
- Inner door shelvings (12 mini-shelves)
- Chart recorder

ESCO

WORLD CLASS. WORLDWIDE.

Esco Technologies, Inc. • 2940 Turnpike Drive, Units 15-16 • Hatboro, PA 19040, USA
Toll-Free USA and Canada 877-479-3726 • Tel 215-441-9661 • Fax 215-441-9660
us.escoglobal.com • usa@escoglobal.com

Esco Micro Pte. Ltd. • 21 Changi South Street 1 • Singapore 486 777
Tel +65 6542 0833 • Fax +65 6542 6920 • mail@escoglobal.com
www.escoglobal.com

Esco Global Offices | Beijing, China | Kuala Lumpur, Malaysia | Manama, Bahrain | Guangzhou, China | Hanoi, Vietnam | Marietta, OH, USA | Melaka, Malaysia | Mumbai, India | Philadelphia, PA, USA | Salisbury, UK | Shanghai, China | Seoul, Korea | Delhi, India | Singapore